

STANDARD SPECIFICATIONS

13.7M FLAT TOP EXTENDABLE TRAILER

TRAILER SPECIFICATIONS:

- | | |
|-------------------------|--|
| ➤ DECK SIZE | 13720MM CLOSED, EXTENDING TO 21220MM OPEN |
| ➤ BEAMS/K-PIN | MAIN BEAM WEBS AND FLANGES ALL GRADE 350 STEEL, 10MM WEBS IN NECK AREA AND 6MM REMAINDER, BOLT ON SKIDPLATE 1420MM PIN SETTING WITH 50MM DEMOUNTABLE PIN AND BOLT ON BLOCK PROVISION |
| ➤ SLIDER SPACING | 1500MM INCREMENTS WITH AIR OPERATED LOCKS WITH ENGAGEMENT INDICATORS AND LOCK CONTROLS IN LOCKABLE BOX |
| ➤ BEARERS/ STRINGERS | 100MM TFB BEARERS WITH 30X30X2.5 RHS STRINGERS |
| ➤ FLOOR | 3MM STEEL CHECKER PLATE ALL OVER |
| ➤ COAMINGS | 125 X 65MM TFB COAMING WITH NO LIP |
| ➤ SIDE STEPS | SIDE STEP EACH SIDE AT REAR OF DECK & EACH SIDE OF DECK SPLIT |
| ➤ TIE RAILS | 25MM MBPE PIPE TIE RAILS AND 50X20X3 RHS SIDE PLATES |
| ➤ FRONT/REAR LOAD RACKS | PROVISION FOR FRONT AND REAR LOAD RACKS |
| ➤ TOOL BOX | TOOL BOXES ARE 1.6MM STEEL, HAVE FULLY WELDED BOTTOMS AND ARE ATTACHED WITH HIGH TENSILE BOLTS |
| ➤ SPARE WHEEL CARRIER | FLAT BAR TYPE SPARE WHEEL CARRIER WITH SCREW IN WHEEL CLAMPS |
| ➤ AXLES | 22.5" K HITCH DRUM BRAKE AXLES WITH GREASE HUBS |
| ➤ SUSPENSION | 1384MM SPREAD K-HITCH MECHANICAL SUSPENSION WITH 9 LEAF SPRINGS |
| ➤ BRAKES | ADR APPROVED REMOTE MOUNT BRAKE KIT |
| ➤ RIMS | 22.5" MULLINS ROAD KING STEEL RIMS PAINTED SILVER (5YR WARRANTY) |
| ➤ TYRES | 11R22.5" HANKOOK TYRES |
| ➤ MUD FLAPS | STANDARD STEEL ¼ GUARDS & MUD FLAPS FRONT & REAR OF TRI |
| ➤ LANDING LEGS | 2 SPEED JOST D200 LANDING LEGS |
| ➤ LIGHTING | FULL HELLA LED SIDE LIGHTS, INDICATORS AND REAR LIGHTS |
| ➤ ELECTRICS | MULTI VOLT |
| ➤ SIGNAGE | OVER SIZE SIGN ON REAR OF TRAILER, BEACON ON SWITCH WIRED TO PARKERS FITTED TO REAR AND STANDARD REAR MARKER PLATES TO ADR REGULATIONS |
| ➤ PAINTING | SANDBLASTED AND PAINTED IN 2-K PAINT TO CUSTOMERS COLOURS |