

STANDARD SPECIFICATION

SINGLE DRIVE RIGID TILT SLIDE TRAY

TRAY SPECIFICATIONS:

- **HEADBOARD** 3MM PLATE CAB HEIGHT HEADBOARD WITH 2X TOOLBOXES AT BASE
- **DECK SIZE** APPROX 7500MM LONG TRAY, 2500 MM WIDE
- **FLOOR** 6MM HARDOX 450 FLOOR
- **MAIN RAILS** 180 X 75 PFC MAIN RAILS
- **TIPPING FRAME** 125 X 125 X 6 RHS TIPPING FRAME WITH ANTI TWIST SCISSOR BRACING
- **SUB FRAME** 75 X50X5 RHS SUBFRAME
- **COAMING** PROFILED GRADE 350 10MM PLATE COAMING RAILS WITH 100X50 PFC STIFFENER
44MM COAMING LIP ABOVE FLOOR
- **TIE RAILS/POINTS** 25MM MBPE TIE RAILS AND 12 KEY HOLE TIE POINTS IN FLOOR
- **STEPS** FRONT STEPS AND GRAB RAILS AT FRONT OF TRAY
- **HYDRAULICS** LIFT AND SLIDE CYLINDERS 4" BORE X 2" ROD, SLIDE CYLINDER 3.7M STROKE
- **WINCH** 20,000LB APE WINCH WITH AIR OPERATED CLUTCH, 16MM CABLE AND SPRING
CABLE TENSIONER
- **SPARE WHEEL CARRIER** SPARE WHEEL WINCH RE FITTED TO CHASSIS IF SUPPLIED
- **LIGHTING** LED SIDELIGHTS & SIDE INDICATORS, WORK LIGHTS & TWIN ROTATOR BEACONS
ON HEADBOARD WITH ORIGINAL LIGHTS AND REVERSE BEEPER OFF TRUCK
RE FITTED TO REAR
- **PAINTING** SANDBLASTED AND PAINTED IN 2-K PAINT TO CUSTOMERS COLOURS

STANDARD SPECIFICATION

TANDEM DRIVE RIGID TILT SLIDE TRAY

TRAY SPECIFICATIONS:

- **HEADBOARD** 3MM PLATE CAB HEIGHT HEADBOARD WITH 2X TOOLBOXES AT BASE
- **DECK SIZE** APPROX 8000MM LONG TRAY, 2500 MM WIDE
- **FLOOR** 6MM HARDOX 450 FLOOR
- **MAIN RAILS** 200 X 75 PFC MAIN RAILS
- **TIPPING FRAME** 150 X 100 X 6 RHS TIPPING FRAME WITH ANTI TWIST SCISSOR BRACING
- **SUB FRAME** 75 X50X5 RHS SUBFRAME
- **COAMING** PROFILED GRADE 350 12MM PLATE COAMING RAILS WITH 100X50 PFC STIFFENER
44MM COAMING LIP ABOVE FLOOR
- **TIE RAILS/POINTS** 25MM MBPE TIE RAILS AND 12 KEY HOLE TIE POINTS IN FLOOR
- **STEPS** FRONT STEPS AND GRAB RAILS AT FRONT OF TRAY
- **WINCH** 20,000LB APE WINCH WITH AIR OPERATED CLUTCH, 16MM CABLE AND SPRING
CABLE TENSIONER
- **HYDRAULICS** LIFT AND SLIDE CYLINDERS 4" BORE X 2" ROD, SLIDE CYLINDER 3.7M STROKE
- **SPARE WHEEL CARRIER** SPARE WHEEL WINCH RE FITTED TO CHASSIS IF SUPPLIED
- **LIGHTING** LED SIDELIGHTS & SIDE INDICATORS, WORK LIGHTS & TWIN ROTATOR BEACONS
ON HEADBOARD WITH ORIGINAL LIGHTS AND REVERSE BEEPER OFF TRUCK
RE FITTED TO REAR
- **PAINTING** SANDBLASTED AND PAINTED IN 2-K PAINT TO CUSTOMERS COLOURS

JOB CARD

14.6M FLAT TOP SEMI TILT SLIDE TRAILER

TRAILER SPECIFICATIONS:

- DECK SIZE 10620MM TILTING AND SLIDING DECK AND 4000MM FIXED TOP DECK
LOAD ANGLE 11 DEG AND SLIDE TRAVEL 3.7M
- BEAMS/K-PIN MAIN BEAM WEBS AND FLANGES ALL GRADE 350 STEEL, 10MM WEBS IN NECK AREA
AND 6MM REMAINDER, BOLT ON SKIDPLATE 1420MM PIN SETTING WITH 50MM
DEMOUNTABLE PIN AND BOLT ON BLOCK PROVISION
- DECK LOCKS 2X DECK PINS TO LOCATE DECK WHEN DECK DOWN AND FORWARD
- BEARERS 75x75x4 RHS BEARERS
- FLOOR 6MM HARDOX 450 DECK
- COMBING 12MM GRADE 350 PROFILED COMBINGS WITH 12MM LIP ABOVE FLOOR
- TWISTLOCKS YES, 3 POSITIONS FOR 20' CONTAINER 1 POSITION FOR 40' CONTAINER
- TIE RAILS/POINTS 25MM MBPE TIE RAILS WITH TIE POINTS IN COAMINGS AND KEY HOLE PLATES
IN FLOOR
- FRONT LOADRACKS FIXED FRONT HEADBOARD 450MM HIGH
- TOOL BOX TOOL BOXES ARE 1.6MM STEEL, HAVE FULLY WELDED BOTTOMS AND ARE
ATTACHED WITH HIGH TENSILE BOLTS
- WATER TANK 70L PLASTIC WATER TANK
- WINCH 1x 30,000LB WINCH MOUNTED ON FRONT OF FIXED DECK
SPRING CABLE TENSIONER AND CLUTCH
FULLY REMOTE CONTROL
- AXLES 22.5" TMC DRUM BRAKE 285PCD 10 STUD AXLES WITH GREASE HUBS
- SUSPENSION 1300MM SPREAD TMC AIR SUSPENSION WITH WEIGHT GAUGE & RAISE
LOWER VALVE
- RIMS 22.5" 10 STUD MULLINS STEEL RIMS PAINTED SILVER (5YR WARRANTY)
- TYRES 255/70R22.5" HANKOOK TYRES
- SPRAY SUPPRESSION STEEL QUARTER GUARDS AND MUD FLAPS
- LANDING LEGS 2 SPEED JOST D200 LANDING LEGS WITH ROCKER FEET
- LIGHTING LED SIDE LIGHTS, INDICATORS AND HELLA P/N.2422 LEDS ON REAR. LIGHTS ON
HYDRAULIC VALVE MOUNT TO ILLUMINATE CONTROLS AT NIGHT
- VOLTAGE 12 VOLT WITH FULL FUNCTION REMOTE CONTROL AND REVERSE BEEPER
- SIGNAGE REAR MARKER PLATES AS PER ADR REGULATIONS
- PAINTING SANDBLASTED AND PAINTED IN 2-K PAINT TO CUSTOMERS COLOURS.

JOB CARD

14.6M SEMI TILT SLIDE TRAILER

TRAILER SPECIFICATIONS:

- DECK SIZE 10620MM TILTING AND SLIDING BOTTOM DECK AND 4000MM FIXED TOP DECK
LOAD ANGLE 9 DEG AND SLIDE TRAVEL 3.7M
- BEAMS/K-PIN MAIN BEAM WEBS AND FLANGES ALL GRADE 350 STEEL, 10MM WEBS IN NECK AREA
AND 6MM REMAINDER, BOLT ON SKIDPLATE 1420MM PIN SETTING WITH 50MM
DEMOUNTABLE PIN AND BOLT ON BLOCK PROVISION 940MM BEAM CENTRES
- DECK LOCKS 2X DECK SUPPORTS TO POSITION DECK LEVEL WITH TOP DECK FOR LOADING
- BEARERS 75x75x4 RHS BEARERS
- FLOOR 6MM HARDOX 450 TOP DECK AND 6MM HARDOX 450 BOTTOM DECK
- COMBING 12MM GRADE 350 TOP AND BOTTOM DECK PROFILED COMBINGS WITH 12MM LIP
ABOVE FLOOR
- TWISTLOCKS YES, WITH PEDISTALS - 3 POSITIONS FOR 20' CONTAINER 2 POSITIONS FOR 40'
CONTAINER
- TIE RAILS/POINTS TOP DECK 25MM MBPE TIE RAILS WITH 2 TIE POINTS IN COAMINGS AND 6 KEY HOLE PLATES
IN FLOOR
- TIE RAILS/POINTS BOTTOM DECK NO TIE RAILS WITH 12 TIE POINTS IN COAMINGS AND 14 KEY HOLE PLATES IN
FLOOR
- FRONT LOADRACKS FIXED FRONT HEADBOARD 450MM HIGH
- TOOL BOX FABRICATED 3MM CHECKER PLATE TOOLBOX BETWEEN BEAMS AT FRONT
- WATER TANK 70L PLASTIC WATER TANK
- WINCH 2x 20,000LB WINCHES MOUNTED ON FRONT OF BOTTOM DECK
SPRING CABLE TENSIONERS AND CLUTCHES
FULLY REMOTE CONTROL
- AXLES 19.5" TMC DRUM BRAKE 275PCD 8 STUD AXLES WITH GREASE HUBS
- SUSPENSION 1300MM SPREAD 150 R/H TMC AIR SUSPENSION WITH WEIGHT GAUGE & RAISE
LOWER VALVE
- RIMS 19.5" 8 STUD MULLINS STEEL RIMS PAINTED SILVER (5YR WARRANTY)
- TYRES 245/70R19.5" HANKOOK TYRES
- SPRAY SUPPRESSION STEEL QUARTER GUARDS AND MUD FLAPS
- LANDING LEGS 2 SPEED JOST D200 LANDING LEGS WITH ROCKER FEET
- LIGHTING LED SIDE LIGHTS, INDICATORS AND HELLA P/N.2422 LEDS ON REAR. LIGHTS ON
HYDRAULIC VALVE MOUNT TO ILLUMINATE CONTROLS AT NIGHT
- VOLTAGE 12 VOLT WITH FULL FUNCTION REMOTE CONTROL AND REVERSE BEEPER
- SIGNAGE REAR MARKER PLATES AS PER ADR REGULATIONS
- PAINTING SANDBLASTED AND PAINTED IN 2-K PAINT TO CUSTOMERS COLOURS.