

STANDARD SPECIFICATIONS

11M WIDENING FLOAT TRAILER

TRAILER SPECIFICATIONS:

- DECK SIZE APPROX 11000MM DECK PLUS RAMPS.
2500MM WIDE WIDENING TO 3500MM WITH PHASING HYDRAULIC CYLINDERS
- BEAMS/K-PIN MAIN BEAM WEBS AND FLANGES ALL GRADE 350 STEEL 10MM WEBS IN NECK AND 8MM REMAINDER 150x20MM FLANGES TOP AND BOTTOM
WELD ON SKID PLATE 50MM OR 90MM LIFT OUT KINGPIN
- BEARERS 250MM UB37 BEARERS AND 6MM GRADE 350 PRESSED BEARER SLEEVES
- FLOOR 5MM CHECKER PLATE FLOOR
- COAMING 12MM GRADE 350 PROFILE CUT COAMINGS
- TIE RAILS NO TIE RAILS, APPROX. 20 TIE POINTS IN COAMINGS
- TOOL BOX NO TOOLBOXES
- SPARE WHEEL CARRIER (IF OPTIONED) DOUBLE STACKED WHEEL CARRIER ON GOOSENECK
- AXLES 19.5" TMC DRUM BRAKE AXLES WITH GREASE HUBS
- SUSPENSION 1232MM SPREAD TMC MECHANICAL SUSPENSION WITH 9 LEAF SPRINGS
- BRAKES ADR APPROVED REMOTE MOUNT BRAKE KIT
- RIMS 19.5" 8 STUD MULLINS ROAD KING STEEL RIMS PAINTED SILVER (5YR WARRANTY)
- TYRES 245/70R19.5" HANKOOK TYRES
- MUD GUARDS STEEL ¼ GUARDS AND MUD FLAPS FRONT AND REAR OF TRI
- LANDING LEGS MANUAL FABRICATED LANDING LEGS
- ELECTRICS FULL HELLA LED SIDE LIGHTS, INDICATORS AND REAR LIGHTS
- REAR RAMPS HYDRAULIC REAR RAMPS 3000x900MM 180MM CHANNEL FRAME 6MM GRADE 350 TOP PLATES WITH 16MM GROUSER BARS
- POWER PACK 12 VOLT POWER PACK MOUNTED IN GOOSENECK WITH SINGLE N70ZZ BATTERY, ISOLATION SWITCH AND TRICKLE CHARGE THROUGH 7 PIN PLUG
- SIGNAGE REVERSIBLE CLIP ON OVERSIZE SIGN WITH FLASHING AMBER BEACON WIRED TO SWITCH ON PARKERS FITTED TO RAMPS WITH REAR MARKER PLATES TO ADR REGULATIONS
- PAINTING SANDBLASTED AND PAINTED IN 2-K PAINT TO CUSTOMERS COLORS